

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (Currently Amended) A method for delivering content over a network having at least one requesting endpoint and at least one node, wherein the content further comprises a descriptor ~~that comprises an ONIX code and~~ that enables the at least one node to identify an attribute of the content and wherein the at least one node stores content, the method comprising:

launching a request for content from the at least one requesting end point,  
the step of launching a request ~~further~~ comprising:

launching the request with a request payload containing one or  
more instructions on what to locate in the descriptor, wherein  
the descriptor comprises an ONIX code descriptor and the at  
least one node further comprises a receiver for receiving the  
request and identifying an adjacent node from which the  
request is received;

comparing the request payload to the ONIX code descriptor of the  
content stored at the at least one node; and when the  
request payload matches the ONIX code descriptor,

forwarding the content with the matching ONIX code descriptor to  
the adjacent node;

propagating the request over the network to the at least one node;

leaving a trail of the request at the at least one node; and, when content matching the request is located,

returning a copy of the content to the at least one requesting endpoint over the trail of the request.

2. (Original) The method of claim 1, wherein the network comprises at least one other endpoint and the method further comprises:

propagating the request over the network to the at least one other endpoint; and

leaving a trail of the request at the at least one other endpoint.

3. (Cancelled)

4. (Previously Presented) The method of claim 1, further comprising:

launching the request with a persistence indicator that indicates a duration for which the request is to be preserved at the at least one node.

5. (Original) The method of claim 4, wherein the step of leaving a trail of the request further comprises:

storing the request at the at least one node for a duration given by the persistence indicator.

6. (Cancelled)

7. (Currently Amended) A system for delivering content over a network having at least one requesting endpoint and at least one node, wherein the content further comprises a descriptor ~~that comprises an ONIX code and~~ that enables the at least one node to identify an attribute of the content and wherein the at least one node stores content, the system comprising:

a request launcher for launching a request for content from the at least one requesting end point, the request launcher ~~further comprises~~ comprising:

a launch module for launching the request with a request payload containing one or more instructions on what to locate in the descriptor, wherein the descriptor comprises an ONIX code descriptor and the at least one node further comprises a receiver for receiving the request and identifying an adjacent node from which the request is received;

a comparator for comparing the request payload to the ONIX code descriptor of the content stored at the at least one node; and

a forwarder for forwarding, when the request payload matches the ONIX code descriptor, the content with the matching ONIX code descriptor to the adjacent node;

a propagator for propagating the request over the network to the at least one node;

a request trailer for leaving a trail of the request at the at least one node; and, when content matching the request is located,

a content forwarder for returning a copy of the content to the at least one requesting endpoint over the trail of the request.

8. (Cancelled)

9. (Previously Presented) The system of claim 7, further comprising:

a persistence indicator that indicates a duration for which the request is to be preserved at the at least one node.

10. (Original) The system of claim 9, wherein the request trailer further comprises:
- a storage module to enable storing the request at the at least one node for a duration given by the persistence indicator.
11. (Cancelled)
12. (Currently Amended) An article of manufacture for delivering content over a network having at least one requesting endpoint and at least one node, wherein the content further comprises a descriptor ~~that comprises an ONIX code and that~~ enables the at least one node to identify an attribute of the content and wherein the at least one node stores content, the article of manufacture comprising:
- at least one processor readable carrier; and
- instructions carried on the at least one carrier;
- wherein the instructions are configured to be readable from the at least one carrier by at least one processor and thereby cause the at least one processor to operate so as to:
- launch a request for content from the at least one requesting end point the launch further comprising:
- launching the request with a request payload containing one or more instructions on what to locate in the descriptor, wherein the descriptor comprises an ONIX code descriptor and the at least one node further comprises a receiver for receiving the request and identifying an adjacent node from which the request is received;

compare the request payload to the ONIX code descriptor of the  
content stored at the at least one node; and when the  
request payload matches the ONIX code descriptor,

forward the content with the matching ONIX code descriptor to the  
adjacent node;

propagate the request over the network to the at least one node;

leave a trail of the request at the at least one node; and, when content  
matching the request is located,

return a copy of the content to the at least one requesting endpoint over  
the trail of the request.

13. (Cancelled)

14. (Currently Amended) A method for transferring content over a network  
comprising one or more nodes, wherein the content further comprises a  
descriptor ~~that comprises an ONIX code and~~ that enables the one or more nodes  
to identify an attribute of the content and wherein the one or more nodes are  
enabled to route messages related to the transfer of content, the method  
comprising the steps of:

transmitting a content registration message when new content is available  
at the one or more nodes, wherein the content registration  
message advertises to the one or more nodes that the new content  
is available;

transmitting a request registration message containing one or more  
instructions on what to locate in the descriptor when requesting  
content from the one or more nodes, wherein the request

registration message advertises to the one or more nodes an interest in locating a particular attribute of the content as identified by the descriptor, and wherein the descriptor comprises an ONIX code;

transmitting a content deliver message when the particular content requested is located at the one or more nodes; and

transferring the particular content requested or a copy of the particular content requested toward the one or more nodes from which the request registration message was transmitted.

15. (Original) The method of claim 14, wherein the step of transmitting a content registration message further comprises:

propagating the content registration message to the one or more nodes;  
and

building a routing table entry at the one or more nodes using the content registration message.

16. (Original) The method of claim 14, wherein the step of transmitting a content registration message further comprises:

propagating the request registration message to the one or more nodes;  
and

building a routing table entry at the one or more nodes using the request registration message.

17. (Original) The method of claim 14, wherein the step of transmitting a request registration message further comprises:

creating a request registration message trail.

18. (Original) The method of claim 17, wherein the one or more nodes are enabled to store messages and wherein the step of creating a request registration message trail further comprises:

storing a copy of the request registration message at each of the one or more nodes that route the request registration message.

19. (Original) The method of claim 17, wherein the step of transferring the particular content requested or a copy of the particular content requested toward the one or more nodes from which the request registration message was transmitted further comprises:

routing the particular content requested or a copy of the particular content requested along a path marked by the request registration message trail.

20. (Cancelled)

21. (Original) The method of claim 14, further comprising:

balancing the network load for transferring content by storing copies of content at the one or more nodes.